

COMPARATIVE CHART OF OT-2300, OT-2200, OT-2100 ,OT-2000 AND OT-2000L (2015Mar.Update)

	OT-2300	OT-2200	OT-2100	OT-2000	OT-2000L
					
SPECIFICATIONS					
Table Dimension					
Length	2120 mm	2125 mm	2125 mm	2125 mm	2125 mm
Width	600 mm	600 mm	600 mm	600 mm	600 mm
Table Top Elevation(with mattress) / Electric Hydraulic	675~1095 mm	740~1040 mm	740~1040 mm	755~1055 mm	540~940 mm
Trendelenburg/ Reverse Trendelenburg / Electric Hydraulic	27°/ 27°	20°/ 20°	20°/ 20°	25°/ 25°	20°/ 20°
Lateral tilt (Left/ Right) / Electric Hydraulic	27°/27°	20°/20°	20°/20°	20°/20°	20°/20°
Lower Back Section (Up/Down) / Electric Hydraulic	80°/50°	80°/30°	80°/30°	80°/45°	80°/30°
Upper Back Section (Up/Down) / Electric Hydraulic	40°/50°	N.A	N.A	N.A	N.A
Head Section (Up/Down) Manual	25°/90°	25°/90°	25°/90°	25°/90°	25°/90°
Foot Plate (Up/Down)	0°/90° (Electric Hydraulic)	20°/90°(Manual)	20°/90°(Manual)	20°/90°(Manual)	20°/90°(Manual)
Flex/ Reverse Flex / Electric Hydraulic	205°/80°(Auto-setting)	210°/90° (Auto-setting)	N.A	N.A	N.A
Split Angle / (Foot Plate) / Manual	N.A	245°	245°	245°	245°
Table Top Sidewise Slide (Left/Right) / Electric Hydraulic	N.A	150 mm	N.A	N.A	N.A
Table top longitudinal slide (Left/Right) / Electric Hydraulic	N.A	350 mm	350 mm	N.A	N.A
4 electro-hydraulic floor locking castors	YES	YES	YES	YES	YES
Auto-Resetting "0" position of table top	YES	YES	YES	YES	YES
ACCESSORIES					
Emergency Override Panel	Standard	Standard	Optional	Optional	Optional
UPS Battery Device	Standard	Standard	Optional	Optional	Optional
Hand controller	Standard	Standard	Standard	Standard	Standard
Armrest/2 pcs	Standard	Standard	Standard	Standard	Standard
Screen Frame	Standard	Standard	Standard	Standard	Standard
Knee crutches	Option	Standard	Standard	Standard	Standard
Headrest	Standard	Standard	Standard	Standard	Standard
Shoulder support/2 pcs	Option	Standard	Standard	Standard	Standard
Body Support	Option	Standard	Standard	Standard	Standard
Mattress	Standard	Standard	Standard	Standard	Standard
Lateral support	Option	Standard	Standard	Standard	Standard

Additional Accessories (option)					
Wireless remote Controller(no. Ot-1832)	YES	N.A	N.A	N.A	N.A
Foot support (no. Ot-1724)	YES	YES	YES	YES	YES
Cylindrical support/s.s. (no. Ot-1726)	YES	YES	YES	YES	YES
Raised armrest/s.s. (no. Ot-1728)	YES	YES	YES	YES	YES
Funnel and wast receptacle and corrugated tubing/s.s. (no. Ot 1718)	YES	YES	YES	YES	YES
U-shaped headrest/s.s. (no. Ot-1720)	YES	YES	YES	YES	YES
Head cushion (no. Ot-1723)	YES	YES	YES	YES	YES
Kidney elevator (no. Ot-1740)	YES	YES	YES	YES(OT-1624)	YES(OT-1624)
Waterproof Foot Pedal controller	YES	N.A	N.A	N.A	N.A
Wrist support (For Ophthalmic position)	YES	YES	YES	YES	YES
Sitting head support (no Ot-1732) (For Sitting position)	YES	YES	YES	YES	YES
Chest/abdominal support (no. Ot-1730)	YES	YES	YES	YES	YES
Instrument tray/s.s. (no. Ot-1725)	YES	YES	YES	YES	YES
Abdominal support (no. Ot-1727)	YES	YES	YES	YES	YES
Table top x-ray radiography sheets (no. Ot-1729)	YES	YES	YES	YES	YES
Table for hand and arm surgery/s.s. (no. Ot-1719)	YES	YES	YES	YES	YES
Restraint strap (no. Ot-1620)	YES	YES	YES	YES	YES
Infusion rod/s.s. (no. Ot-1721)	YES	YES	YES	YES	YES
Orthopaedic device with cart for lower limbs/s.s. (no. Ot-090)	N.A	YES	YES	YES	YES
Orthopaedic device with cart for lower limbs and forearm/s.s. (no. Ot-080)	N.A	YES	YES	YES	YES
Physical Properties					
Table weight (approx) kgs	285	285	285	170	285
Mattress Thick	5.5 cm	5.5 cm	5.5cm	5.5 cm	5.5 cm
Patient Weight capacity	250 Kgs.	250 Kgs.	250 kgs.	180 kgs.	250 kgs.
Power requirements					
Electrical AC Input	110~230V	110~230V	110~230V	110~230V	110~230V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Remote Control Power(no. Ot-1832)	12 Vdc	N.A	N.A	N.A	N.A
Safety Standards	CE, FDA, GMP	CE, FDA, GMP	CE, FDA, GMP	CE, FDA, GMP	CE, FDA, GMP